



SPECS

FRAME	
SIZES	SM / MD / LG / XL
COLOUR	PURPLE
FRAME	SERIES 2 CUSTOM BUTTED AND HYDROFORMED 6061 ALLOY TUBESET
FORK	FOX 36 PERFORMANCE ELITE / 140mm TRAVEL / 15 X 110mm
REAR-SHOCK	N/A
HEADSET	PRESTINE PT-F13
COMPONENTS	
HANDLEBARS	RACEFACE NEXT R CARBON 35 / 780mm / 35mm
STEM	RACEFACE TURBINE 35 / 50mm
GRIPS	ODI ELITE MOTION
SADDLE	SARACEN CUSTOM CRMO MTB
SEATPOST	KS LEV INTEGRA / 150mm TRAVEL (125mm ON S SIZE) / 30.9mm
PEDALS	N/A
DRIVE TRAIN	
SHIFTERS	SHIMANO XT M8100 / 1 X 12 SPEED
REAR-DERAILLEUR	SHIMANO XT M8100 / 12 SPEED
FRONT-DERAILLEUR	N/A
CHAINSET	SHIMANO XT FC-M8120 / 32T / 170mm
CHAIN	KMC X12
CASSETTE	SHIMANO XT M8100 / 12 SPEED / 10-51T
BRAKES	SHIMANO XT M8120
BRAKE-LEVERS	SHIMANO XT M8100
WHEELS	
RIMS	DT SWISS EX511 / 32H / 29" FRONT / 27.5" REAR
HUBS	KT HUBS BOOST 15X110 32H FRONT / KT HUBS M8110-B 12X148 32H REAR
SPOKES	SPOKES DOUBLE-BUTTED STAINLESS STEEL
TYRES	TYRES MAXXIS MINION DHRIL / EXO / TR / 29 X 2.3" FRONT / 27.5 X 2.3" REAR

FEATURES

- Low Slack Long (LSL) inspired geometry utilizing our Series 2 custom butted and hydroformed 6061 alloy tubeset
- Fork: Fox 36 Performance Elite, 140mm travel, HS/LS adjust, 15 x 110
- Drivetrain: Shimano XT / SLX 12 Speed, 10-51T
- Brakes: Shimano XT M8120, 180/180mm
- Components: Raceface Next R 35 Carbon bar and Turbine stem, ODI grips, KS Lev Integra dropper post

GEOMETRY

SIZE	S	M	L	XL
SEAT TUBE (mm)	360	410	460	510
TOP TUBE (mm)	609	637	664	687
REACH (mm)	440	465	490	510
STACK (mm)	629	638	647	656
HEAD TUBE (mm)	95	105	115	125
HEAD ANGLE (°)	64	64	64	64
SEAT ANGLE (°)	75	75	75	75
CHAINSTAY (mm)	440	440	440	440
BOTTOM BRACKET (mm)	20/45	20/45	20/45	20/45
WHEELBASE (mm)	1201	1230	1260	1284
HEAD SET	ZS44-ZS56	ZS44-ZS56	ZS44-ZS56	ZS44-ZS56
AXLE TO CROWN (mm)	551	551	551	551
OFFSET (mm)	42-44	42-44	42-44	42-44
FORK TRAVEL (mm)	140	140	140	140

The image above is for illustration purposes only. Saracen reserves the right to change spec, colour, features and price without prior warning.

MANTRA RACE

TECHNICAL INFORMATION

SARACEN

MODEL	ZENITH ELITE LSL
FRAME MATERIAL	AL-6061
RECOMMENDED / MAX FORK LENGTH	547 mm / 550mm
OFFSET	44mm
RECOMMENDED / MAX FORK TRAVEL	29": 140mm
MAXIMUM TYRE	27.5" X 2.5"
BRAKE MOUNT TYPE	POST160
MAX REAR ROTOR	180mm
SEAT POST	30.9mm
SEAT COLLAR	34.9mm
BOTTOM BRACKET TYPE	BSA73
ISCG	NA
CRANK CHAINLINE	BOOST
MAX CHAIN RING	34T
REAR HUB TYPE	12 X 148



MANTRA RACE

SPARE PARTS

PART NUMBER	DESCRIPTION	QTY NEEDED	TORQUE	NOTES
RNS4049	HANGER	1	-	-

CLICK TO BUY
SPARE PARTS ON
SARACEN.CO.UK

SUSPENSION

SETUP GUIDE

FORK // Fox 36 Performance Elite

CLICK FOR
SUSPENSION
SET-UP GUIDE

The image above is for illustration purposes only. Saracen reserves the right to change spec, colour, features and price without prior warning.